


閃

閃 ETOILE

RITMICA[®]
WOOD




The Ritmica Wood partition wall is entirely made of wood and has a separating function. It comes in three different versions, glazed or solid.




RITMICA® WOOD D1
central glass

RITMICA® WOOD D2
double glass

RITMICA® WOOD SOLID
double solid partition








CHARACTERISTICS

- 1.** Thickness: 92 mm
- 2.** Veneered laminated wood structure
- 3.** Wood slats are joined with the “finger joint” technique
- 4.** Floor profiles are in 6060 UNI 9006/1 extruded aluminium, concealed to ensure impermeability
- 5.** 2 versions of glazed partitions - single central glass and double glass
- 6.** 1 solid version in melamine-finished or veneered panels, 18 mm thick
- 7.** 2 thicknesses can be used for safety-glass or acoustic modules
- 8.** Fixed corner profiles
- 9.** Vertical junctions between glazed elements, made of wood, polycarbonate or transparent two-sided tape
- 10.** Door frame with cable routing
- 11.** Utility module
- 12.** 5 versions of hinged doors - solid, tempered glass and framed
- 13.** 3 versions of external sliding doors - solid, tempered glass and framed

RITMICA® WOOD D1







- 01.** Thickness: 92 mm
- 02.** Veneered laminated wood structure
- 03.** Wood slats are joined with the “finger joint” technique
- 04.** Floor profiles are in 6060 UNI 9006/1 extruded aluminium, concealed to ensure impermeability
- 05.** Single central glass - 55.1/55.2/66.1/66.2 laminated glass or 10-12-mm-thick tempered glass
- 06.** Fixed corner profiles
- 07.** Vertical junctions between glazed elements, made of wood, polycarbonate or transparent two-sided tape
- 08.** Door frame with cable routing
- 09.** Utility module
- 10.** 5 versions of hinged doors - solid, tempered glass and framed
- 11.** 3 versions of external sliding doors - solid, tempered glass and framed




Wall-end uprights




Fixed wall-end upright

Wall-end uprights



End profile




Storage-end upright


Junction profiles



40



Junction
Ritmica Wood D1 - Ritmica Wood D1



Junction
Ritmica Wood D1 - Ritmica Wood Solid

Junction profiles



adjustable


**Polycarbonate
junction profile**

**Two-sided technical tape
junction**

**Polycarbonate
three-way junction**

**Two-sided technical tape
three-way junction**


Corner profiles




Wooden 90° corner profile
single central glass



Wooden 90° corner profile
solid/single glass



Two-sided technical tape
90° corner junction




Polycarbonate
90° corner profile



Cabling and utility module for hinged doors



Utility module



Cabling solution




*possible positions for switches and sockets on the door frame


Cabling and utility module for sliding doors



Utility module



Cabling solution



*possible positions for switches and sockets on the door frame

RITMICA® WOOD D2




Plus and Acoustic performance





- 01.** Thickness: 92 mm
- 02.** Veneered laminated wood structure
- 03.** Wood slats are joined with the “finger joint” technique
- 04.** Floor profiles are in 6060 UNI 9006/1 extruded aluminium, concealed to ensure impermeability
- 05.** Double glass - 55.1/55.2/66.1/66.2 laminated glass or 10-12-mm-thick tempered glass
- 06.** Fixed corner profiles
- 07.** Vertical junctions between glazed elements, made of wood, polycarbonate or transparent two-sided tape
- 08.** Door frame with cable routing
- 09.** Utility module
- 10.** 5 versions of hinged doors - solid, tempered glass and framed
- 11.** 3 versions of external sliding doors - solid, tempered glass and framed

- 01.** Laminated glass 66.2 - **47 dB**



Wall-end uprights



Fixed wall-end upright


*double 55.1/55.2 laminated glass
double 66.1/66.2 laminated glass*

*10-mm-thick tempered glass
12-mm-thick tempered glass*

Wall-end uprights



End profile



Storage-end upright

Junction profiles



40

Junction
Ritmica Wood D2 - Ritmica Wood D2

Junction
Ritmica Wood D2 - Ritmica Wood Solid

Junction profiles



adjustable


**Polycarbonate
junction profile**

**Two-sided technical tape
junction**


**Polycarbonate
three-way junction**

**Two-sided technical tape
three-way junction**


Corner profiles




**Wooden 90° corner profile
double glass**



**Wooden 90° corner profile
solid/double glass**



**Two-sided technical tape
90° corner junction**




**Polycarbonate
90° corner profile**



Cabling and utility module for hinged doors



Utility module



Cabling solution




*possible positions for switches and sockets on the door frame

Cabling and utility module for sliding doors



Utility module



Cabling solution




*possible positions for switches and sockets on the door frame

RITMICA® WOOD SOLID







- 01.** Thickness: 92 mm
- 02.** Veneered laminated wood structure
- 03.** Wood slats are joined with the “finger joint” technique
- 04.** Floor profiles are in 6060 UNI 9006/1 extruded aluminium, concealed to ensure impermeability
- 05.** Solid wall in melamine-finished or veneered panels - 18 mm thick
- 06.** Fixed corner profiles
- 07.** Vertical junctions made of wood between glazed and solid elements, and made of wood or transparent double-sided tape between solid elements
- 08.** Door frame with cable routing
- 09.** Utility module
- 10.** 5 versions of hinged doors - solid, tempered glass and framed
- 11.** 3 versions of external sliding doors - solid, tempered glass and framed




Wall-end uprights




Fixed wall-end upright

Wall-end uprights




End profile




Storage-end upright

Junction profiles



Junction profiles



A diagram showing a horizontal junction of two grey panels. The junction is formed by a vertical strip of grey tape applied to the edges of both panels, creating a double-sided tape connection.


**Two-sided technical tape
junction**



A diagram showing a vertical junction of three grey panels. The junction is formed by a vertical strip of grey tape applied to the edges of the two outer panels, creating a three-way tape connection.

**Two-sided technical tape
three-way junction**


Corner profiles




**Wooden 90° corner profile
double solid panel**



**Wooden 90° corner profile
solid/single glass**



**Wood-wood
90° corner junction**




**Wooden 90° corner profile
solid/double glass**



Cabling and utility module for hinged doors



Utility module



Cabling solution




*possible positions for switches and sockets on the door frame



Cabling and utility module for sliding doors



Utility module



Cabling solution



*possible positions for switches and sockets on the door frame


RITMICA[®]
WOOD

Doors and handles


FRAMES FOR HINGED DOORS




Door frame on **Ritmica Wood D1**





Door frame on **Ritmica Wood D2**




Door frame on **Ritmica Wood Solid**




SOLID DOOR LEAF 43 mm thick


SOLID DOOR LEAF 43 mm thick




ML1




ML4




ML5




ML6




ML7




ML8




ML9




ML10




ML11




MLQ




MLT

SOLID DOOR LEAF 92 mm thick**CHARACTERISTICS**


- 01.** concealed hinge
- 02.** visible or concealed door closer
- 03.** switch on door upright
- 04.** recessed dust seal




SOLID DOOR LEAF 92 mm thick




ML5




ML6




ML7




ML8




ML9




ML10




ML11




MLQ




MLT


TEMPERED GLASS DOOR LEAF_ANODIZED FULL-HEIGHT HINGE 10 mm thick

TEMPERED GLASS DOOR LEAF_ANODIZED FULL-HEIGHT HINGE 10 mm thick


MC1




MC4




MC5




MC5V




MC6




MC6V




MC7




MC7V




MC8




MC8V




MC9




MC9V




MC10




MC10V




MC11




MC11V




MCQ





MCQO




MCT




MCTO

FRAMED SINGLE-GLASS DOOR LEAF 43 mm thick


FRAMED SINGLE-GLASS DOOR LEAF 43 mm thick




ML5




ML6




ML7





ML8




ML9




ML11

FRAMED DOUBLE-GLASS DOOR LEAF 92 mm thick**CHARACTERISTICS**


- 01.** concealed hinge
- 02.** visible or concealed door closer
- 03.** switch on door upright
- 04.** recessed dust seal




FRAMED DOUBLE-GLASS DOOR LEAF 92 mm thick




ML5




ML6




ML7



ML8



ML9




ML11


FRAMES FOR SLIDING DOORS




Door frame on **Ritmica Wood D1**




Door frame on **Ritmica Wood D2**




Door frame on **Ritmica Wood Solid**




SOLID DOOR LEAF 43 mm thick

TEMPERED GLASS DOOR LEAF 10 mm thick




LARGE FRAMED DOOR LEAF 43 mm thick




Glass door


STEEL




MPOMGH1_H2_H3




MPOM2




MPOM3



MPOMGH1Q_GH2Q_GH3Q




MPOM3Q




MPOM8

ALUMINUM



MPOMTH1_TH2




MPOMQH1_QH2




Solid door


STEEL




MPOMGH1_H2_H3



MPOM2




MPOMGH1Q_GH2Q_GH3Q




MPOM8


ALUMINUM




MPOMTH1_TH2



MPOMQH1_QH2




MPOM4




MPOM5

RITMICA[®]
WOOD


Accessories

Overhead door closer


01 external sliding closer
for framed/solid door




02 concealed closer
for framed/solid door

Floor-mounted door closer


01 floor-mounted
for solid door

Aluminium hinges


01 concealed
for framed/solid door



02 full-height hinge
for tempered glass door

Accessories


01 concealed soundproofing draft stopper
for framed/solid door



02 door stopper
for solid/framed/tempered glass door

RITMICA[®]
WOOD


Finishes

Anodised


01 Natural aluminium



02 Bronze




03 Black



04 Custom colour

RAL Finishes

01 White



02 Black



03 Custom colour

Polish

01 Shine

Wood

01 Light oak




02 Dark oak


Solid panels




CAT. 1




055 Graphite black



420 Gunmetal



418 Ash grey




419 Light grey




393 Dove grey



417 Vanilla



429 Warm white




428 Cold white

CAT. 2




422 Silver




423 Champagne



CAT. 1



421 Eucaliptus



426 Mid-tone oak



274 Acacia



416 Streaked white

CAT. 2



425 Dark walnut



318 Mid-tone walnut



427 Light walnut



382 Natural oak

CAT. 3




138 Aged saw-cut oak



197 Saw-cut eucaliptus



408 Grey oak



400 Danube oak



414 Red walnut



412 Vintage oak



413 Champagne oak



410 Light oak



CAT. 2



304 Dark-tone fabric



123 Mid-tone fabric



305 Light-tone fabric




424 Oxide

CAT. 3



385 Bronze linen



409 Bark



406 Primo fiore grey



405 Primo fiore dove grey



404 Primo fiore beige



415 Desert



01 Clear



02 Extra light



05 Smoked



03 Satin



04 Bronze



06 Custom painted



RITMICA® WOOD is a partition is entirely made of wood, and is **92 mm thick**; it only provides a separating function and is available in **three different versions**.

VERSIONS

RITMICA® WOOD D1

Wood guide profile for single glass, thickness: 55.1/55.2/66.1/66.2 laminated glass or 10-12-mm-thick tempered glass

RITMICA® WOOD D2

Wood guide profile for double glass, thickness: 55.1/55.2/66.1/66.2 laminated glass or 10-12-mm-thick tempered glass

RITMICA® WOOD SOLID

Wood guide for double 18-mm-thick particle-board solid panels

GENERAL DESCRIPTION

This 92-mm-thick wall is entirely made of **solid laminated wood** (floor and ceiling rails, uprights, wall starts) joined together using the finger joint technique to ensure mechanical resistance and compensation of deformations. The floor rails are fitted with concealed 6060 UNI 9006/1 extruded aluminium profiles that provide protection against water infiltration and levelling.

The profiles are designed to accommodate safety-glass closing panels and full solid panels or other monolithic materials as requested by the customer.

The floor and ceiling **rails** and wall profiles allow for perfect levelling of the wall both horizontally and vertically, as well as excellent sealing against existing walls.

The system is equipped with fixed vertical **corner profiles** and linear junction solid wood profiles whose function is to increase the junction mechanical resistance and ensure closure.

Two-way and three-way **linear connection** elements are added to these junctions. They are made of polycarbonate or transparent two-sided tape.

Doors can be either hinged or sliding, full-height or standard height.

Both types of doors can be single-leaf, double asymmetrical/reduced leaf or double-leaf.



Hinged doors can be made of wood, framed single glass or double glass or glass only. The framed version allows for the installation of recessed overhead door closers and lower acoustic dust seals; on the glazed version only an external door closer can be installed.

The **sliding version** can be made of wood, single framed glass or flush glass. Correct sliding is ensured by soft-stop mechanisms for closing and opening the doors.

The 43-mm-thick **honeycomb-core wood door** has an internal honeycomb structure inserted in a firwood perimeter frame and fibreboard panels on both sides, finished with HPL laminate edged and ABS edges. Thickness=10/10 mm.

The **framed glass door** has perimeter solid wood profiles, of different width, and an internal tempered or laminated glass (4+4 mm), clear or frosted.

Wooden or framed-glass doors are supplied with different types of hinges: hinges concealed in the frame, hinges adjustable on three axes, with 180° opening.

The **glass door** is made with a 10-mm-thick tempered glass panel, with clear or frosted finish. The hinges provided for the flush doors are aluminium or steel linear hinges, with 180° opening.

Door jambs, made of solid wood profiles, allow the routing of wires and the insertion of single-pole controls.

To allow for adequate **cable management** inside the wall, a **utility module** in extruded aluminium is provided to facilitate the installation of switches, sockets, thermostats, alarm sensors and other dimensionally compatible equipment.

Doors can be matched to a wide **range of standard handles** that can be further expanded thanks to the use of locks with a universal plate, suitable for the installation of out-of-catalogue items.

These walls can be perfectly **integrated** with the Quadra storage system.



01. Double glass partition 66.2 (laminated 6+6+pvb 0.76) - Acoustic test -
Certificate no. 432259 IT/EN - UNI EN ISO 10140-2:2021 and UNI EN ISO 717-1:2021



Etoile s.r.l. - Società Unipersonale

Via Delle Industrie, 9/B 61040 Sant'Ippolito (PU) Italy
P. +39.0721.85.59.34
info@etoilesrl.it - www.etoilesrl.it